IEA Weyburn CO₂ Monitoring and Storage ProjectLong-term Assessment of Fate of CO₂: Treatment of Abandoned Wells



Mike Stenhouse, Wei Zhou, Monitor Scientific LLC Rick Chalaturnyk, Francisco Moreno, University of Alberta Waleed Jazrawi, Project Director, PTRC

2nd Annual Conference on Carbon Sequestration, Hilton Alexandria, May 5-8, 2003








Outline of Talk

- Introduction to Weyburn EOR
- Assessment framework (methodology)
- Abandoned wells issues and treatment
- Integration of results (planned!)






Weyburn Unit



(Slide courtesy of EnCana)




Field Size: 70 sq. miles

CO₂ injection started Sept. '00 CO₂ injected: 49 bcf (Dec. '02)





Rollout of the CO₂ Flood



Monitor Scientific



Weyburn EOR - Introduction

SW

Weyburn Midale Field

Reservoir and Trapping Components

Weyburn Fjeld (footprint) **Triassic (Lower Watrous)** Frobisher Evaporite Zone oi Mesozoic alteration **Poplar** Miss. Ratcliffe Beds Upper Midale (Marly) Midale Evaporite **NOTE:** Vertical scale exaggerated Lower Midale (Vuggy) (Slide courtesy of Geoff Burrowes, EnCana) Frobisher Vuggy Frobisher Marly



NE

Long-Term Assessment: Context

• PERFORMANCE MEASURES

- Environmental-global: whether any leakage of CO₂ compromises GHG reduction objectives
- Environmental-local: whether any leakage of CO₂ represents an environmental risk to the local population (CO₂ concentration in air, water quality, toxic metal release)

• TIMESCALE


- Governs what processes should be considered
- Hundreds to thousands of years (modeling up to 5,000 years)





Long-Term Assessment Framework

- Systems Analysis
- Define Weyburn CO₂
 'System'
 - storage field + surrounding geosphere + surface/nearsurface environment, including atmosphere
- Identify possible ways in which the System can evolve
 - Base Scenario
 - Alternative Scenarios






Vertical Extent of Weyburn System








Map of Wellbores (Phase 1A)








Weyburn - Base Scenario



- Defined as the "expected evolution of the Weyburn CO₂ storage system"
 - CO₂ migration pathways will be a combination of *natural* and *man-made* pathways
 - Wellbore casing seals will be assumed not to leak at time zero
 - CO₂ rock water interactions (long-term geochemical modeling)



Possible Leakage Paths for CO₂




Probabilistic Treatment of CO₂ Leakage via Abandoned Wells

- Not all wells are, or will be, equal
- Need to address heterogeneities in
 - Transport parameters
 - Reservoir rock
 - Wellbore and annular seals (evolution with time)
 - Fluid distribution in reservoir
 - Hydraulic connection between wellbore and surrounding formations (metal casing corrosion)





"Unit Cell" Representation of Abandoned Well







Approach to Abandoned Wells

- Detailed study being carried out by University of Alberta (UofA), using 'real' data to:
 - examine conditions of wellbores, both pre-CO₂
 injection and post-CO₂ injection (EOR) phases
 - predict impact of geomechanical and geochemical effects on transport properties and, hence, leakage of CO₂
- UofA results will then be used by Monitor Scientific (MSCI) as input to long-term assessment






Wellbore Leakage: Information / Data Input

- Well file information (well file database)
- Digital records (logs, production, injection)
- Simulation results (reservoir)
- Geologic 3-D Model
- Analytical Models (e.g. geochemical, geomechanical)
- Numerical Models (e.g. borehole stability)
- Laboratory Experiments











Wellbore Annulus Seal Heterogeneity


Wrong density




Poor mud/filter-cake removal




Premature gelation




Excessive fluid loss




Highly permeable slurry




High shrinkage



Cement failure under stress




Poor interfacial bonding



Source: Oilfield Review, 2002



Assessment of Wellbore Leakage



Abandoned Wells: Long-Term Evolution Chemical/Geochemical Changes

- Degradation of cement (casing seals, annular seals)
 - Carbonation, attack by sulphate, chloride
 - Changes in porosity, permeability will affect transport properties of seals
- Corrosion of metal casing
 - Ultimately, localized casing failure will allow hydraulic connection with surrounding formations






Interaction of Supercritical CO₂ with Cement

- Overall effect comprises accelerated carbonation, depth penetration, and even greater porosity reduction than under 'natural' conditions
- Mechanical effects?
 - possible brittle nature of carbonated cement phases?
 - potential for cracking?






Process Modelling: CO₂ Flow in Wells



Conceptual model


Results format
[Flux =f(P)]





Integration of results

Assessment of Abandoned Wells: Output – Combined Wells



Hypothetical output

- "Real" field data (well files, production data, etc.), combined with analytical or numerical simulations, used to quantify the likelihood of "leakage" from individual wells.
- Focus attention on higher risk areas for post-CO₂ injection phase assessment





Phase 1A Results: Input to Long-Term Assessment

- Extrapolation of detailed (Phase 1A) results to entire assessment area
 - Assume similar statistics for Phase 1A predictions apply to rest of field (assumption can be tested)
- Use predicted well flux rates as distributed sinks with respect to CO₂ migration modeling in the geosphere





Acknowledgements

 The long-term assessment relies on information/data being provided by almost all Research Providers involved in the IEA CO₂ Monitoring and Storage Project







